



## Interior/Exterior Wood Filler

**Description:** LePage® Interior/Exterior Wood Filler is a quality synthetic latex wood filler for cracks, holes and surface imperfections. It is a smooth, buttery paste that spreads and feathers easily and dries to match most light coloured wood. Interior/Exterior Wood Filler can be sanded, stained, painted, varnished, drilled, nailed and screwed. It will not shrink or crack up to an 18 mm (3/4") application. LePage® Interior/Exterior Wood Filler has a low odour and wet product can be easily cleaned with soap and water. It is weatherproof and mould and mildew resistant.

### Available As:

Item #	Size	Package
462071	162 ml	Squeeze Tube
462072	225 ml	Plastic Tub
462073	500 ml	Plastic Tub

### Recommended For:

LePage® Interior/Exterior Wood Filler is used for filling cracks, scratches and nail holes in wood, drywall and plaster. It can be used to level wood grain and chipped or gouged surfaces before painting.

### For Best Results:

- Not recommended for continuous water immersion
- Not recommended for use on floors, caulk, sealant or as a joint filler over cracks and joints where expansion and contraction may occur
- Do not use for exterior application if rain is expected within 24 hours
- Not recommended for chinking between logs in log cabins or tuck pointing applications on brick
- Not recommended for use on painted or primed surfaces
- Not recommended for use as a skim coat
- Not recommended for use on traffic areas (indoor or outdoor)
- Not suitable for application to horizontal deck boards
- Wood fills will not mimic wood grain and color will vary from surrounding wood. Test for acceptability.

### Features & Benefits:

- Weatherproof for All-Season Durability
- Tan Color Blends with Most Light Colored Wood
- Water and Crack Resistant
- Can be Screwed, Nailed or Sanded
- Can be Painted, Stained or Varnished to Blend with Surroundings



# TECHNICAL DATA SHEET

## Typical Uncured Physical Properties:

Color:	Tan
Appearance:	Paste
Base:	Synthetic polymer
Odor:	Characteristic
Specific Gravity:	0.86
% Solids by Weight:	66%
pH:	7.7
Viscosity:	425 Mcps @ 1 rpm
Shelf Life:	18 months from date of manufacture (unopened)
Lot Code Explanation:	<b>YYDDD</b>
Stamped on lid of can	<b>YY=</b> Last two digits of year of manufacture <b>DDD=</b> Day of manufacture based on 365 days in a year Example: 14061 = 61 <sup>st</sup> day of 2014 = March 2, 2014

## Typical Application Properties:

Application Temperature:	Apply above 10°C (50°F)
Dry Time:	A 2 mm (1/16") to 3 mm (1/8") depth dries in approximately 3 hours An 18 mm (3/4") depth dries in approximately 24 hours Dry time is dependent upon temperature, humidity and thickness of application

## Typical Cured Performance Properties:

Color:	Light tan
Service Temperature:	-18°C (0°F) to 66°C (150°F)
Water Resistant:	Yes. Recommended to paint with an exterior paint for long life.
Sandable:	Yes

## Directions:

### Tools Typically Required:

Utility knife, putty knife, 80 and 120 grit sandpaper.

### Safety Precautions:

Keep out of reach of children.

### Preparation:

Apply above 10°C (50°F). Surfaces must be clean, dry and free of grease, dust and other contaminants. Do not apply wood filler on painted or primed surfaces. Wood filler may be tinted using water-based tints or dry pigments. If using squeeze tube format, remove cap and cut nozzle at a 45° angle to desired size.

### Application:

Using a putty knife, work filler into cracks and holes. If filling holes deeper than 18 mm (3/4"), apply filler in two or more applications. Allow each layer to dry before applying the next. For best results, overfill the final layer above the surface and sand level once dry. When sanding, start with 80 grit sandpaper followed by 120 grit. Sand in a circular motion to avoid grooving patch. Paint, stain or varnish once dry. When staining, the wood filler may absorb the stain differently than the surrounding wood. Test a small area first or experiment with a dried sample of wood filler until desired effect is achieved. For exterior applications, protect wood filler with paint, stain or varnish.

### Clean-up:

Clean hands and tools immediately with soap and water. Cured filler may be carefully cut away with a sharp-edged tool or sanded.

## Storage & Disposal:

DAMAGED BY FREEZING. Store above freezing. Close the tube or lid tightly after each use. Product should not be washed down the drain. To dispose of unwanted product, scrape or squeeze out remaining material, allow to dry and discard with trash. Rinse and wipe container and place with plastics for recycling.



# TECHNICAL DATA SHEET

---

**Label Precautions:**      **KEEP OUT OF REACH OF CHILDREN**

Refer to Material Safety Data Sheet (MSDS) for further information.

---

**Disclaimer:**

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.



---

LePage Brand is part of the Henkel family of brands. Founded in 1876, Henkel is a global leader in the consumer and industrial businesses. Henkel operates worldwide with leading brands and technologies in three business areas: Laundry & Home Care, Beauty Care and Adhesive Technologies.

Henkel Canada Corporation - Professional & Consumer Adhesives Headquarters – Mississauga, ON L5N 6C3  
[www.henkelna.com](http://www.henkelna.com)

Revision Date: 07/11/2014    Supercedes: 07/17/2013    Ref. #: 252835 / 1399-3 (Tub)    957979 / WDW6200 (Tube)